

GEVA 75 Irrigation Window Controller



General Description

Stand-alone battery driven irrigation controller timer with a G75 2WNC 9VDC latch coil connected. Powered by a single 9V battery. Can operate any valve equipped with 3/4" UNEF solenoid cavity (Richdel[®] type).

Notes

- Dust and water tight.
- Various mounting options, on valve and wall.
- High quality alkaline battery included.
- Irrigation window function, plus manual operation.
- Please consult our technical sales department for further information on compatibility with various coils.



Mounting Options



Wall Mounting



Vertical Mounting



Horizontal Mounting

How to Order

Example : G75-C-262

Is a Geva 75 Irrigation window controller with 1" slip in PVC valve.

G75-C	Type	Valve	
	Irrigation Window	2	
		No valve	00
		3/4"BSP	50
		1"BSP	60
		1"NPT	61
		1" Slip in	62

Technical Specifications

Mechanical

Mounting : Directly on a 30mm diameter solenoid in horizontal or with adaptor or wall mounting by four screws. Required accessor

Dust and water tight, to IP67 and NEMA 4X

Operating temperature: - 10° to 60° C

Integrated four keys keypad.

Electrical

Batteries : One 9V alkaline battery. Use top quality type to en autonomous operation. One 3.0V Lithium memory backup battery.

Screw-in wire connection.

Low battery warning

Power saving LCD

Software

24 hours real time clock.

Irrigation Window:

- Set start and end hours
- Set on time (1 sec to 99 min)
- Set off time (1 min to 12 hr)
- Select effective days.